

The Model NSR66-PS Position Switch

Specifications

The Model NSR66-PS Position Switch is utilized to monitor the position of heavy moving machinery such as a gravity take-up or a tripper car. The micro switch used in the products is approved by VDE, products are produced as accordance with CE standards. Also It meets EAC standards for the Russian market. Once the roller actuator arm is moved from its normal position the micro switches are tripped. The micro switches can be used to send an alarm to the control system or operator telling it or them to either

shut off or move the piece of heavy machinery. The NSR66-PS Position Switch is commonly found on tripper floors to annunciate the position of the tripper car ensuring that the material is being unloaded in the correct spot. They are also utilized as a limit switch to protect gravity take-ups on conventional conveyors from bottoming out. The NSR66-PS Position Switch is essentially a heavy duty limit switch and has a variety of uses in industrial.

Technical Specifications

- Body : Aluminum Casting NEMA-4
- Micro Switch Values : 15A @ 115-230 VAC, 30 VDC ↻
- Output Signal : (2) SPDT shutdown (Alarm, Closure)
- Cable Entry : 2xM25
- Movement Angle : 15° - 25°
- Temperature Rating : -42° - 80°C
- Mounting Structure : It is suitable for double-sided use.
- Protection Class : IP67

Applications

Conventional Conveyor Belts
 Piston Conveyors
 Shuttle Conveyors
 Ship Loading / Unloading Systems
 Stockpile / Reclaim Systems
 Crawler Conveyors
 Heavy Duty Applications

Approvals for Safety

Meets Electrical Safety	IEC 60204-1: 2005-10
	IEC 60947-1: 2004-03
Meets Mechanical Safety	IEC 60204-1: 2005-10
Meets Functional Safety	IEC 60204-1: 2005-10
Meets Outdoor/Noise/Vibration Certificate	IEC 60529: 2001-02



Product Image



Dimensions

